



INTERIOR-WAX

Hard-wearing finish with a wax-like character for wood for interior use!



7393 White
transparent



7394 White
Satin



Product description:

Transparent or opaque, satin and hard-wearing wood finish with a wax-like character for indoor areas. Osmo Interior-Wax is stain-resistant, water-repellent and abrasion-resistant and smoothens the surface. The wood grain remains visible. Simple application – no primer or sanding between coats needed – this saves time and money. Suitable for wood; microporous surface will not crack, peel or flake. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

Recommended use:

Osmo Interior-Wax is suitable for the protection and decorative finishing of wood in indoor areas: wall and ceiling panelling, moulding and beams as well as furniture, doors and children's toys. It is also suitable for recoating and repairing wood factory finished with Osmo Interior-Wax White Transparent (7393) or White Opaque (7394) and for recoating old wooden ceiling panelling.

Ingredients:

On the basis of a polymer dispersion, waxes, titanium dioxide (white pigment) additives and preservatives (MIT/ BIT). Solvent: water. This product fulfils EU-Regulation (2004/42/EC) according to the VOC limit value max. 130 g/l (Cat. A/e (2010)). Full declaration of ingredients on request.

Technical Data:

Specific gravity: 1.10-1.25 g/cm³
Viscosity: 1300-1700 mPas viscid
Odour: faint/mild, odourless after drying
Flashpoint: not required
pH value: 8,0-9,0

Storage:

2 years and longer if stored in the closed original can. Do not expose to frost or temperatures above 30 °C!

Surface Preparation:

Wood surface must be clean and dry (maximum moisture content 18 %). Clean or slightly sand old finishes. Trial application recommended. If there is insufficient gradient or insufficient adhesion, the old coat has to be removed. Always wear a dust mask while sanding. Small cracks, larger dents and small holes in the wood can be filled Osmo Wood Filler. Remove dust etc. thoroughly from the surface before application. Apply on frost-free wood only, and at temperatures of at least 10 °C. Osmo Interior-Wax is ready to use, please do not thin, stir well before use. The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

Methods of Application:

With either Osmo Flat Brush or Osmo Microfibre Roller apply thinly and evenly along the wood grain and spread well. Allow to dry for approx. 3 - 4 hours. If necessary, do a fine-grained (P 360) sanding between coats. After drying apply a second thin coat as before. Due to the quick drying properties, do not make sections too wide. For renovations 1 coat will be sufficient for most cases.

Cleaning of tools:

Immediately after use, with soap and water.



Drying time:

Approx. 3-5 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times.

Coverage:

Product coverage for 1 coat is 16 m²/1 l. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

Note:

One coat of Interior-Wax White Opaque creates a more intensive colour than two coats of Interior-Wax White Transparent.

Caution:

Keep out of reach of children. Contains 1,2-benzisothiazol-3(2H)-one (BIT), 2-methyl-2H-isothiazol-3-one (MIT). May cause an allergic skin reaction. Wear protective gloves. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. If skin irritation or rash occurs: Get medical advice/attention. If medical advice is needed, have product container or label at hand.

Disposal:

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 12). Only completely emptied cans can be recycled.

Colour tone:

7393 White transparent
7394 White opaque

Size:

0.75 l; 2.5 l

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 11/19



Warning